



your local global brand

# Gulf Syntrac 4T 10W-40

*Fully synthetic 4-stroke Motorcycle Oil*

## Product Description:

**Gulf Syntrac 4T 10W-40** is a fully synthetic, 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance air cooled 4-stroke motorcycles and is blended from premium quality base stocks and advanced additive technology to exceed the most demanding lubrication requirements of modern 4-stroke motorcycles. **Gulf Syntrac 4T 10W-40** provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and is suitable in a wide range of ambient temperatures. **Gulf Syntrac 4T 10W-40** exceeds the specifications of API SL and JASO MA/MA2 and the requirements of leading global 4-stroke motorcycle manufacturers.

**Gulf Syntrac 4T 10W-40** outstanding thermo-oxidative stability minimises deposits and controls oil thickening facilitating extended engine and oil life, has exceptional antiwear properties protecting vital engine and gear components leading to reduced maintenance costs. Controlled frictional properties eliminate clutch slippage leading to increased power/fuel economy and improves driveability. Special detergents/dispersants used in **Gulf Syntrac 4T 10W-40** ensures cleaner pistons leading to faster heat dissipation and longer engine life. Excellent shear stability maintains viscosity under high temperature/high shear environment and provides improved wear protection. Outstanding low temperature properties enables easy starting at low ambient temperatures and ensures effective lubrication and wear protection at start up. Low volatility characteristics reduces oil consumption and hydrocarbon pollution. Effective rust and corrosion inhibition properties ensures longer life of critical engine components.

**Gulf Syntrac 4T 10W-40** is recommended for advanced 4-stroke gasoline engines in high performance motorcycles of leading global manufacturers operating in a wide range of ambient temperatures.

## Meets the specifications of: API SL, JASO MA

<u>Properties:</u>	<u>Test Methods:</u>	<u>Typical Values:</u>
SAE Viscosity Grade	SAE J300	10W-40
Density @ 15°C	ASTM D4052	850 kg/m <sup>3</sup>
Kinematic Viscosity @ 40°C	ASTM D445	90.1 mm <sup>2</sup> /s (cSt)
Kinematic Viscosity @ 100°C	ASTM D445	14.2 mm <sup>2</sup> /s (cSt)
Low-Temperature Cranking Viscosity @ -25°C	ASTM D5293	<7000 mPa.s (cP)
Viscosity Index	ASTM D2270	>155
Flash Point	ASTM D92	>205°C
Pour Point	ASTM D97	<-33°C
Total Base Number	ASTM D2896	9.75 mgKOH/g
Sulphated Ash	ASTM D874	1.21 wt %

Product Code: 1297

Date Issued: 25/06/2012

Date Superseded: 22/02/2012

Revision nr: 03