



# SAPPHIRE SPRAY GREASE

**Multipurpose EP grease, fortified with PTFE, in an aerosol.  
Designed for the effective lubrication and protection of all moving parts  
such as bearings & slides operating in a wide variety of applications.**

## FEATURES

- Ø Temperature range  $-50^{\circ}\text{C}$  to  $200^{\circ}\text{C}$
- Ø Outstanding EP performance (355kg weld load)
- Ø Sapphire Premier in an aerosol can
- Ø Suitable for use as an electrical contact lubricant
- Ø Excellent corrosion protection
- Ø Ideal for linear bearings

## DIRECTIONS FOR USE

- Ø Shake well, hold upright and spray from a distance of 10-20 cms
- Ø Ensure adequate ventilation
- Ø Do not spray on a naked flame or any incandescent material
- Ø Check compatibility with painted or coated surfaces, plastics and rubbers if the product is liable to contact these materials

## Technical and Safety Data Sheets are available from:

**Fax Back Facility** : +44 (0)113 232 2770  
**Web Site** : [www.ocol.com](http://www.ocol.com)  
**Customer Service** : +44 (0)113 232 2700

Issue 34305d: Jan-04

1

### **ROCOL Lubricants**

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

[www.ocol.com](http://www.ocol.com)

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.  
There are many factors outside our control or knowledge which affect the use and performance  
of our products, for which reason it is given without responsibility.



# SAPPHIRE SPRAY GREASE

## TECHNICAL DATA (typical values)

Appearance	Thin, light beige, greasy film
Base type	Synthetic hydrocarbon fluid
Thickener	Lithium complex soap
Solids	PTFE
Propellant	Hydrocarbon
Solvent	Isoparaffinic Hydrocarbon
Temperature range	-50 <sup>0</sup> C to 200 <sup>0</sup> C
Storage	Storage temperature should be kept below 50 °C. Storage area should be: out of direct sunlight.
Pack sizes	400 ml

Issue 34305d: Jan-04

2

### **ROCOL Lubricants**

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

[www.ocol.com](http://www.ocol.com)

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.  
There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA