

PRODUCT DESCRIPTION

Xtreme TRUCK SYNT 5W30 LOW SAPS is a latest generation synthetic lubricant made with carefully selected raw materials and formulated with additives (UHPDO: Ultra High-Performance Diesel Oil) with low ash content for high performance diesel engines with low emissions, improve efficiency and extend the life of exhaust emissions systems such as diesel particulate filter (eg DPF - Diesel particulate filter). This product exceeds the performance standards required by the major commercial vehicle manufacturers.

Xtreme TRUCK SYNT 5W30 LOW SAPS guarantees:

- Prolonged periods of oil change and better fuel efficiency,
- Maximum protection against wear and friction,
- Increased engine cleanliness,
- Excellent low temperature fluidity,
- Maintaining the viscosity at high temperatures,
- Oxidation stability,
- Cutting resistance and stability of viscosity,
- Energy savings.

APPLICATIONS

Xtreme TRUCK SYNT 5W30 LOW SAPS is ideal for a fleet of vehicles which are SAE 30 lubricants that meet the demands of specific requirements E6, E7 and E9. In addition, this product is recommended for all new engine technology and the most advanced European integration bus with low levels of polluting emissions. Further it can be used for driving and previous generations bus.

PERFORMANCE LEVELS AND APPROVALS

**ACEA E6/E7/E9-16
API CJ-4
MB 228.51
MAN M3477 & M3271-1
MTU Type 3.1**

**MACK E0-N - E0-M Plus
Deutz DQC IV-10LA
RENAULT VI RLD-2 -TRUCKS RXD, RGD
VOLVO VDS-3 - CNG**

TYPICAL CHARACTERISTICS

Parameter	Measure unit	Testing procedure	Results
SAE grade	-	-	5W-30
Density	kg/L	ASTM D 1298	0,854
Kinematic viscosity @100°C	mm ² /s	ASTM D 445	11,5
Viscosity index	-	ASTM D 2270	160
Pour point	°C	ASTM D 97	-33
Flash point	°C	ASTM D 92	≥ 210
T.B.N.	mgKOH/g	ASTM D 2896	≥ 9

Le schede di sicurezza di tutti i prodotti sono disponibili su richiesta.