



7005 5W-30

PRODUCT DESCRIPTION

Xtreme 7005 5W-40 is a premium quality synthetic multi-grade lubricant blended with base oil after a severe hydrogenated isomerisation process and selected additives.

The high quality of base oil adopted and of additives utilized assure that the product can show very good in service performances on engines fuelled by gasoline or diesel, naturally aspirated or turbocharged, in passenger cars and in light vans.

This product gives the following main benefits:

- *suitable low temperature property to enable rapid lubrication after cold starting,*
- *high oxidation resistance and wear protection to maximize engine life,*
- *good detergency / dispersion properties for the best control of soot.*

APPLICATIONS

Xtreme 7005 meets the specifications reported below.

This product is intended for use in typical service of gasoline and diesel engines operating under vehicle manufacturers' recommended maintenance procedures.

It is suitable for extended drain intervals as specified by the engine manufacturers and for use in high performance gasoline and direct injection diesel engines.

SPECIFICATIONS

**API SL/CF
FORD 913 A/B**

ACEA A1/B1/A5

TYPICAL CHARACTERISTICS

Xtreme 7005	Method	Typical values
SAE Viscosity Grade		5W-30
Density at 15°C, Kg / m ³	ASTM D 1298	≥ 855
Viscosity at 40°C, cSt	ASTM D 445	70
Viscosity at 100°C, cSt	ASTM D 445	9.3 ÷ 12.5
Viscosity Index	ASTM D 2270	≥ 145
Pour Point, °C	ASTM D 97	≤ -30
Flash Point , °C	ASTM D 92	≥ 210

The reported figures are typical of those obtained with normal production tolerance and therefore may be subjected to variation; they do not constitute a specification, exception made for the SAE VG.

MSDS are available upon request.

Rev. 3 – 02/10/2013