

**PRODUCT DESCRIPTION**

Xtreme CVT is a synthetic fluid for continuously variable transmissions suitable to meet the requirements of a wide variety of vehicles equipped with push-belt and chain CVTs.

Xtreme CVT shows following properties:

- High oxidation stability,
- High stable viscosity index,
- Excellent Extreme Pressure and anti-wear performance,
- Good properties at low temperature,
- Good compatibility with metals and seals used,
- Good balanced coefficient friction.

**APPLICATIONS**

Xtreme CVT was developed for use in the latest generation of CVT transmissions.

The main advantages are:

- Superior anti-shudder durability for enhanced driving comfort,
- High level of both torque capacity and anti-shudder performance that provide:
  - ✓ Higher safety factor
  - ✓ Longer transmission life
  - ✓ Extended service interval

**PERFORMANCE LEVELS AND APPROVALS**

BMW Mini Cooper EZL 799A/83 22 0 136 376 Cherry CVT Dodge/Jeep/Chrysler NS-2 Dodge/Jeep/Chrysler/Jeep/Mopar CVT+4 GM/Saturn DEX-CVT Hyundai/Kia CVT-1 Hyundai/Kia SP III (CVT model) Nissan KTF-1 Nissan NS-1,NS-2,NS-3  Toyota CVTF TC Audi Multitronic	Daihatsu AMMIX CVTF DFE/CVT fluid DC/TC Honda HMMF without start clutch/HCF2 Mazda JWS 3320 MG Rover EM-CVT Mini Cooper EZL 799/EZL 799A/ZF CVT V1 Mitsubishi CVTF-J1/J4/J4+/SP-III only CVT Renault Elf Matic CVT/CVT CK-SK-FK Subaru iCVT/ iCVT FG/ECVT/NS-2 Suzuki CVTF 3320/CVTF 4401/TC/NS-2/CVT Green 1&2 Toyota CVTF FE VW/Audi TL 521 16 (G052 516)/TL 521 80 (G052 180 A2)
---	---

**TYPICAL CHARACTERISTICS**

Xtreme CVT FLUID	TESTING PROCEDURE	TYPICAL VALUES
Density @15°C, kg/m <sup>3</sup>	ASTM D 1298	845,0
Kinematic viscosity @40°C, cSt	ASTM D 445	34,0
Kinematic viscosity @100°C, cSt	ASTM D 445	7,1
Viscosity index	ASTM D 2270	178
Viscosity brookfield @-40°C, cP	ASTM D 2983	10000
Flash point, °C	ASTM D 92	210

MSDS of all products are available on request