

PRODUCT DESCRIPTION

Xtreme MOTO 4T 5W40 is a 100% synthetic lubricant formulated with raw materials and additives that ensure maximum performance for 4T engines.

Xtreme MOTO 4T 5W40 guarantees the following features:

- Excellent anti-wear capacity,
- Extraordinary oxidation resistance and thermal stability,
- High detergency / dispersion capacity with resistance to the formation of deposits.

Xtreme MOTO 4T 5W40 has a carefully balanced additive package that offers the following advantages:

- Maximum antifriction protection of group (engine and gearbox-clutch),
- Reduction in oil consumption,
- Reduction in oil degradation with increased engine efficiency,
- Increased useful life of the engine,
- Control over the sliding of the friction discs and protection of the change.

APPLICATIONS

Xtreme MOTO 4T 5W40 is indicated for 4T engines and clutch transmission group of motorbikes of any brand and size. Also, in the latest generation scooters with high performance in the most diverse operating conditions typical of these vehicles as start/stop in city traffic or abruptly accelerations.

PERFORMANCE LEVELS AND APPROVALS

API SM
JASO MA

TYPICAL CHARACTERISTICS

Xtreme Moto 4T 5W40	TESTING PROCEDURE	TYPICAL VALUES
SAE grade		5W-40
Density, kg/m ³	ASTM D 1298	850
Kinematic viscosity, cSt a 40°C	ASTM D 445	80,5
Kinematic viscosity, cSt a 100°C	ASTM D 445	13,5
Viscosity index	ASTM D 2270	172
Pour point, °C	ASTM D 97	-33
Flash point, °C	ASTM D 92	≥ 210

MSDS of all products are available on request